



# TRUCK MOUNT

from the industry-leading innovator



[CEA.NET.AU](http://CEA.NET.AU)



# TRUCK MOUNT

# MACHINE SPECS

| FEATURES                                     | 4000 L                  | 5000 L                  |
|--|-------------------------|-------------------------|
| <b>Mountings</b>                             | Truck & Skid Mounting   | Truck & Skid Mounting   |
| <b>Spoils Capacity (Gal/Ltr)</b>             | 1,050 gal / 4,000 L     | 1,300 gal / 5,000 L     |
| <b>Water Capacity (Gal/Ltr)</b>              | 500 gal / 1,893 L       | 500 gal / 1,893 L       |
| <b>Engine (CAT C2.2)</b>                     | 60 HP Diesel            | 60 HP Diesel            |
| <b>Dual LED work lights and strobe</b>       | Optional                | Optional                |
| <b>Warranty</b>                              | 1 Year                  | 1 Year                  |
| <b>Viper Tool</b>                            | Optional                | Optional                |
| <b>OPERATOR CONTROLS</b>                     |                         |                         |
| <b>Controls Location</b>                     | Curbside                | Curbside                |
| <b>Hour Meter/Tachometer/Vacuum Gauge</b>    | Standard                | Standard                |
| <b>Water Supply Reel</b>                     | Standard                | Standard                |
| <b>Load Level Indicator and Auto Shutoff</b> | Primary Shutoff Only    | Primary Shutoff Only    |
| <b>SPOILS TANK DETAILS</b>                   |                         |                         |
| <b>Hydraulic Hoist Unload</b>                | Standard                | Standard                |
| <b>Full Opening Rear Door</b>                | Standard                | Standard                |
| <b>Rear Door Latch</b>                       | TREX                    | TREX                    |
| <b>Inlet Valve Size/Drain Valve Size</b>     | 6"                      | 6"                      |
| <b>SKID DETAILS</b>                          |                         |                         |
| <b>Height/Length/Width</b>                   | 2,032 / 6,147 / 2,464mm | 2,032 / 6,579 / 2,464mm |
| <b>Height w/ Hydraulic Boom</b>              | 2,794mm                 | 2,794mm                 |
| <b>Empty Weight (Lbs/Kg)</b>                 | 9,865 lbs / 4,475 kg    | 10,464 lbs / 4,747 kg   |
| <b>Mounting Rail Width</b>                   | 849mm                   | 849mm                   |
| <b>Channel Size</b>                          | 10"                     | 10"                     |
| <b>VACUUM PUMP / BLOWER DETAILS</b>          |                         |                         |
| <b>Vacuum Pump/Blower Type</b>               | Positive Displacement   | Positive Displacement   |
| <b>CFM/Hg</b>                                | 1,250 CFM / 16" Hg      | 1,250 CFM / 16" Hg      |
| <b>Reverse Flow</b>                          | Standard                | Standard                |
| <b>Cyclo-Separator Air Filter</b>            | 4: 5 micron filters /   | 4: 5 micron filters /   |
| <b>WATER SYSTEM DETAILS</b>                  |                         |                         |
| <b>Water Pressure/Water Supply</b>           | 4,000 PSI / 22.7 L/Min  | 4,000 PSI / 22.7 L/MIN  |
| <b>Electronic Low Water Shut-Off</b>         | Standard                | Standard                |
| <b>Water Pump Drive</b>                      | Belt Driven             | Belt Driven             |
| <b>Water Supply Hose</b>                     | 15.24mm x 3/8" ID       | 15.24mm x 3/8" ID       |

\*SPECS ON MACHINE MAY CHANGE

[CEA.NET.AU](http://CEA.NET.AU)

# 1250 CFM

| 6000 L                  | 7500 L                  | 10000 L                 | 12000 L                |
|-------------------------|-------------------------|-------------------------|------------------------|
| Truck & Skid Mounting   | Truck & Skid Mounting   | Truck & Skid Mounting   | Truck & Skid Mounting  |
| 1,600 gal / 6,000 L     | 1,981 gal / 7,500 L     | 2,642 gal / 10,000 L    | 3,170 gal / 12,000 L   |
| 500 gal / 1,893 L       | 500 gal / 1,893 L       | 500 gal / 1,893 L       | 500 gal / 1,893 L      |
| 60 HP Diesel            | 60 HP Diesel            | 60 HP Diesel            | 60 HP Diesel           |
| Optional                | Optional                | Optional                | Optional               |
| 1 Year                  | 1 Year                  | 1 Year                  | 1 Year                 |
| Optional                | Optional                | Optional                | Optional               |
| Curbside                | Curbside                | Curbside                | Curbside               |
| Standard                | Standard                | Standard                | Standard               |
| Standard                | Standard                | Standard                | Standard               |
| Primary Shutoff Only    | Primary Shutoff Only    | Primary Shutoff Only    | Primary Shutoff Only   |
| Standard                | Standard                | Standard                | Standard               |
| Standard                | Standard                | Standard                | Standard               |
| TREX                    | TREX                    | TREX                    | TREX                   |
| 6"                      | 6"                      | 6"                      | 6"                     |
| 2,286 / 6,884 / 2,464mm | 2,388 / 6,833 / 2,312mm | 2,388 / 8,078 / 2,312mm | 2,388 / 8,687 / 2,312  |
| 3,048mm                 | 3,150mm                 | 3,150mm                 | 3,150mm                |
| 11,838 lbs / 5,370 kg   | 12,086 lbs / 5,483 kg   | 12,853 lbs / 5,830 kg   | 14,336 lbs / 6,503 kg  |
| 849mm                   | 849mm                   | 849mm                   | 849mm                  |
| 10"                     | 10"                     | 10"                     | 10"                    |
| Positive Displacement   | Positive Displacement   | Positive Displacement   | Positive Displacement  |
| 1,250 CFM / 16" Hg      | 1,250 CFM / 16" Hg      | 1,250 CFM / 16" Hg      | 1,250 CFM / 16" Hg     |
| Standard                | Standard                | Standard                | Standard               |
| 4: 5 micron filters /   | 4: 5 micron filters /   | 4: 5 micron filters /   | 4: 5 micron filters /  |
| 4,000 PSI / 22.7 L/MIN  | 4,000 PSI / 22.7 L/MIN  | 4,000 PSI / 22.7 L/MIN  | 4,000 PSI / 22.7 L/MIN |
| Standard                | Standard                | Standard                | Standard               |
| Belt Driven             | Belt Driven             | Belt Driven             | Belt Driven            |
| 50' x 3/8" ID           | 50' x 3/8" ID           | 50' x 3/8" ID           | 50' x 3/8" ID          |

RING  
O  
MATIC

1300 788 757



# TRUCK MOUNT

6 Function Hydraulic  
Boom

Full Opening  
Rear Door



Connector  
Gate Valve

Hydraulic Actuating  
TRES Locks

Water Tanks

CAT Engine



6" Drain Valve

ENJOY MORE PRODUCTIVITY,  
RELIABILITY, LOCATE  
ACCURACY AND EFFICIENCY  
WITH RING-O-MATIC  
VACUUM EXCAVATION  
MACHINES.

RING-O-MATIC OFFERS A FULL  
LINE OF TRUCK  
MOUNTED UNITS DESIGNED TO  
WITHSTAND THE RIGORS OF  
HEAVY USE IN RUGGED  
TERRAIN. EACH MACHINE  
COMES WITH THE OPTION OF A  
SIX FUNCTION HYDRAULIC  
CONTROLLED BOOM, FULL  
OPENING HYDRAULIC REAR  
DOOR AND AN AMPLE SUPPLY  
OF WATER ON BOARD TO GET  
THE JOB DONE.



BRISBANE  
SYDNEY  
MELBOURNE

ADELAIDE  
PERTH

CEA.NET.AU 1300 788 757

All equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Ring-O-Matic dealer or Corporate sales team for more information about machine specifications. Ring-O-Matic reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. RING-O-MATIC, RING-O-MATIC Corporate logo, Ring-O-Matic Company R logo, PROVEN PERFORMANCE, VIPER and VLX are trademarks of Ring-O-Matic, INC. in the U.S. and / or other countries.